



# The Model T200H High Range Chemiluminescence NO/NO<sub>2</sub>/NO<sub>x</sub> Analyzer



The Model T200H High Range NO / NO<sub>2</sub> / NO<sub>x</sub> analyzer uses the proven chemiluminescence detection principle and advanced electronics to allow accurate, dependable, continuous measurements for high concentration stack gas monitoring and other applications. A high-efficiency stainless steel thermal NO<sub>2</sub> converter provides durable and consistent operation under the harshest conditions (other converter options also available). The T200H may be fitted with an optional, internal paramagnetic O<sub>2</sub> sensor or an infrared absorption CO<sub>2</sub> sensor, reducing integration and operating costs.

— With NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- All other T Series instrument platform features
- Internal stainless steel converter
- Optional external single or dual converter
- Lifetime technical support by phone and email
- Standard two-year warranty
- Optional internal molybdenum converter
- Optional internal O<sub>2</sub> or CO<sub>2</sub> sensor

# T200H Specifications

■ Ranges	Min: 0 - 5 ppm full scale Max: 0 - 5,000 ppm full scale (selectable, independent NO, NO <sub>2</sub> , NO <sub>x</sub> ranges with dual range supported)
■ Measurement Units	ppm, mg/m <sup>3</sup> (selectable)
■ Zero Noise	< 20 ppb (RMS)
■ Span Noise	< 0.2% of reading (RMS) above 20 ppm
■ Lower Detectable Limit	< 40 ppb
■ Zero Drift	< 20 ppb/24 hours
■ Span Drift	< 0.5% of reading/24 hours
■ Response Time	< 80 seconds to 95% (in switching mode)
■ Linearity	1% of full scale
■ Precision	0.5% of reading above 5 ppm
■ Sample Flow Rate	290 cc/min ±10%
■ Power Requirements	100V-120V, 220V-240V, 50/60 Hz, Typical power 160W
■ Analog Output Ranges	10V, 5V, 1V, 0.1V (selectable)
■ Recorder Offset	±10%
■ Included I/O	1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs
■ Optional I/O	1 x USB com port 1 x RS485 4 x digital alarm outputs Multidrop RS232 3 x 4-20mA current outputs
■ Operating Temperature Range	5 - 40°C
■ Dimensions (HxWxD)	7" x 17" x 23.5" (178 x 432 x 597 mm)
■ Weight	Analyzer: 40 lbs (18 kg) External pump: 22 lbs (10 kg)

Specifications subject to change without notice.  
All specifications are based on constant conditions.



**TELEDYNE API**  
Everywhereyoulook™

9970 Carroll Canyon Road ■ San Diego, CA 92131  
Ph. 858-657-9800 Fax 858-657-9816  
Email [api-sales@teledyne.com](mailto:api-sales@teledyne.com)

For more information about the Teledyne API family of monitoring instrumentation products, call us or visit our website at:

[www.teledyne-api.com](http://www.teledyne-api.com)

© 2019 Teledyne API  
Printed documents are uncontrolled. SAL000047D  
(DCN 8120) 07.15.19

