



# Environmental Instruments Overview

## Ultraviolet Fluorescence Instruments

Gas	Model	Ranges (Min/Max)	Applications
Sulfur Dioxide (SO <sub>2</sub> )	T100U	0-5 ppb / 0-20,000 ppb	Trace Level
	T100	0-50 ppb / 0-20,000 ppb	Ambient Level; Dilution CEMS
	T100H	0-10 ppm / 0-5,000 ppm	CEMS High Level
Hydrogen Sulfide (H <sub>2</sub> S), SO <sub>2</sub>	T101	H <sub>2</sub> S: 0-50 ppb / 0-10 ppm SO <sub>2</sub> : up to 0-20 ppm	Ambient Level; CEMS
Total Reduced Sulfur (TRS), SO <sub>2</sub>	T102	TRS: 0-50 ppb / 0-10 ppm SO <sub>2</sub> : up to 0-20 ppm	Ambient Level; CEMS
Total Sulfur (TS)	T108	0-50 ppb / 0-20,000 ppb	Ambient Level

## Chemiluminescence Instruments

Gas	Model	Ranges (Min/Max)	Applications
Nitrogen Oxide (NO), Nitrogen Dioxide (NO <sub>2</sub> ), NO <sub>x</sub>	T200U	0-5 ppb / 0-2,000 ppb	Trace Level
	T200	0-50 ppb / 0-20,000 ppb	Ambient Level; Dilution CEMS
	T200M	0-1 ppm / 0-200 ppm	CEMS Medium Level
	T200H	0-5 ppm / 0-5,000 ppm	CEMS High Level
Reactive Oxides of Nitrogen (NO <sub>y</sub> )	T200U/NO <sub>y</sub>	0-5 ppb / 0-2,000 ppb	Trace Level
Ammonia (NH <sub>3</sub> ), NO, NO <sub>2</sub> , NO <sub>x</sub>	T201	0-50 ppb / 0-2,000 ppb	Ambient Level
Ozone (O <sub>3</sub> )	T265	0-100 ppb / 0-2,000 ppb	Ambient Level
True NO <sub>2</sub> , NO, NO <sub>x</sub>	T200P	0-50 ppb / 0-4,000 ppb	Photolytic Converter
	T200UP	0-5 ppb / 0-2,000 ppb	Trace Level; Photolytic Converter

## Gas Filter Correlation Instruments

Gas	Model	Ranges (Min/Max)	Applications
Carbon Monoxide (CO)	T300U	0-100 ppb / 0-100 ppm	Trace Level; Dilution CEMS
	T300	0-1 ppm / 0-1,000 ppm	Ambient Level; Dilution CEMS
	T300M	0-5 ppm / 0-5,000 ppm	CEMS Medium Level
Carbon Dioxide (CO <sub>2</sub> )	T360	0-2 ppm / 0-2,000 ppm	Ambient Level
	T360M	0-4 ppm / 0-4,000 ppm	CEMS Medium Level

## Ultraviolet Absorption Instruments

Gas	Model	Ranges (Min/Max)	Applications
Ozone (O <sub>3</sub> )	T400	0-100 ppb / 0-10 ppm	Ambient Level
	430	0-100 ppb / 0-20,000 ppb	Ambient Level



# Environmental Instruments Overview

Particulate Instrument			
Gas	Model	Ranges (Min/Max)	Applications
Continuous Real-time PM Mass Monitoring	T640, 640X Option	PM <sub>2.5</sub> , PM <sub>10</sub> , PM <sub>10-2.5</sub> optional PM <sub>1</sub>	Ambient Level

Gas Calibrators and Zero Air Generators			
Gas	Model	Ranges (Min/Max)	Applications
All Gases	T700U	Available MFC's: 0-10 cc/min to 0-20 LPM	Dilution Calibrator; Trace Level
	T700	Available MFC's: 0-10 cc/min to 0-20 LPM	Dilution Calibrator
	T701	0-18 LPM, 30 PSI	Zero Air Generator
	T701H	0-30 LPM, 35 PSI	Zero Air Generator
	T750	Available MFC's: 0-10 cc/min to 0-20 LPM	Portable Dilution Calibrator
	T750U	Available MFC's: 0-10 cc/min to 0-20 LPM	Portable Dilution Calibrator; Trace Level
Ozone (O <sub>3</sub> )	T703	50 ppb to 10 ppm	O <sub>3</sub> Calibrator
	T703U	3 ppb to 10 ppm	O <sub>3</sub> Calibrator; Trace Level
	T753U	2 ppb to 2.5 ppm	Portable O <sub>3</sub> Calibrator; Trace Level

Cavity Attenuated Phase Shift Instruments			
Gas	Model	Ranges (Min/Max)	Applications
True, Direct NO <sub>2</sub>	T500U	0-5 ppb / 0-1,000 ppb	Trace Level
True NO <sub>2</sub> , NO <sub>x</sub> , NO	500	0-5 ppb / 0-1,000 ppb	Ambient Level

Paramagnetic Instrument			
Gas	Model	Ranges (Min/Max)	Applications
Oxygen (O <sub>2</sub> ), optional CO <sub>2</sub>	T802	0-100%	CEMS

All T Series instruments come with NumaView™ Software and NumaView™ Remote Software. Refer to product specification sheets for details. Specifications subject to change without notice. All specifications are based on constant conditions.



9970 Carroll Canyon Road ■ San Diego, CA 92131  
Ph. 858-657-9800 Fax 858-657-9816  
Email [api-sales@teledyne.com](mailto:api-sales@teledyne.com)

For more information about the Teledyne API family of monitoring instrumentation products, call us or visit our website at:

[www.teledyne-api.com](http://www.teledyne-api.com)

© 2019 Teledyne API  
Printed documents are uncontrolled. SAL000076E  
(DCN 8120) 06.05.19

