

CAT-03 Series Catalytic Ozone Destructs

- All Welded Construction
- Self Contained
- Rapid Reaction Time
- No Consumables
- No Maintenance
- Simple Installation

Ideal for Semiconductor Applications

The CAT-O3 series of ozone destructs safely decompose high concentrations of ozone gas to sub-ppm levels that are below recommended ozone safety limits. The catalytic method of decomposition uses a metal oxide catalyst to passively convert the ozone to oxygen.

The CAT-03 series of ozone destructs are made from a welded stainless steel enclosure protected with a heat shield. They are carefully designed to meet the industry's stringent safety performance requirements.

Applications

- CVD TEOS/Ozone
- ALD
- MOCVD
- Ashers
- Wet Benches
- Spray Tools & More







Model	САТ-03-Е	CAT-03-F	CAT-03-G			
Application	Catalytic Ozone Destruct					
Principle of Operation	Catalytic					
Catalyst	Manganese Dioxide Based Compound					
Outlet Concentration	< 0.01 ppm (well below OSHA requirements)					
Material	Aluminum with SS fittings					
Capacity (up to)	20 SLPM at 340 g/Nm3	32 SLPM at 340 g/Nm3	88 SLPM at 200 g/Nm3			
Inlet/Outlets	1/2" stainless steel stubs or 1/2" male VCR	1/2" stainless steel stubs or 1/2" male VCR	3/4" male VCR			
Dimensions*	19"L x 5.13"H x 4"Diameter (482.6 x 130.3 x 101.6 mm)	27.50″L x 5.13″H x 4″Diameter (698.5 x 130.3 x 101.6 mm)	32"L x 7.56"H x 7"Diameter (812.8 x 192 x 177.8 mm)			
External Temperature	Below 30° C or 86° F					
Maintenance	None					
Lifetime	3 to 5 years or longer					
Warranty	1 year					

**Height and Length dimensions include exterior cover and mount*



Ozone Instrumentation for Every Application						
Model	Generator Output	Off Gas Detection	Safety/Leak Detection	Dissolved Ozone	Spot Checking	
465L						
465M						
465H						
454						
452						
430						
W1 + 465L						
470						



9970 Carroll Canyon Road, San Diego, CA 92131 Phone: 858-657-9800 • Fax: 858-657-9816 Email: api-sales@teledyne.com For more information on Teledyne API Instruments, visit our website at:

www.teledyne-api.com/en-us

©2024 Teledyne API Printed documents are uncontrolled. SAL000100C (DCN 8911) 12.03.2024

