

The Model T102 UV Fluorescence TRS Analyzer



The Model T102 TRS analyzer uses the proven UV fluorescence principle to measure Total Reduced Sulfur at levels commonly required for ambient air monitoring.

— With NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- Lifetime technical support by phone and email
- All other T Series instrument platform features
- Standard two-year warranty





T102 Specifications

Ranges TRS	Min: 0-50 ppb full scale Max: 0-10,000 ppb full scale Up to 0-20,000 ppb full scale (selectable, dual range supported)
Measurement Units	ppb, ppm, μg/m ³ , mg/m ³ (selectable)
Zero Noise	< 0.2 ppb (RMS)
Span Noise	< 0.5% of reading (RMS) above 50 ppb
Lower Detectable Limit	< 0.4 ppb
Zero Drift	< 0.5 ppb/24 hours
Span Drift	< 0.5% of full scale/24 hours
Response Time	< 140 seconds to 95%
Linearity	1% of full scale
Precision	0.5% of reading above 50 ppb
Sample Flow Rate	650 cc/min ±10%
Power Requirements	100V-120V, 220V-240V, 50/60 Hz
Analog Output Ranges	10V, 5V, 1V, 0.1V (selectable)
Recorder Offset	±10%
Included I/O	1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs
Optional I/O	1 x USB com port 1 x RS485 4 x digital alarm outputs Multidrop RS232 3 x 4 - 20mA current outputs
Operating Temperature Range	5 - 40°C (with US EPA Approval)
	850°C (external converter)
Dimensions (HxWxD)	Analyzer: 7" x 17" x 23.5" (178 x 432 x 597 mm)
	Converter: 7" x 17" x 23.5" (178 x 432 x 597 mm)
Weight	Analyzer: 37 lbs (16.8 kg)
	Converter: 20 lbs (9.1 kg)

Specifications subject to change without notice. All Specifications are based on constant conditions



9970 Carroll Canyon Road • San Diego, CA 92131 Ph. 858-657-9800 Fax 858-657-9816 Email api-sales@teledyne.com For more information about the Teledyne API family of monitoring instrumentation products, call us or visit our website at:

www.teledyne-api.com

© 2019 Teledyne API Printed documents are uncontrolled. SAL000043D (DCN 8120) 07.29.19

