The Model T200U Trace-Level Chemiluminescence NO/NO₂/NO_x Analyzer



The Model T200U analyzer achieves low level NO / NO₂ / NO_x measurements using the proven Chemiluminescence principle and advanced electronics. The T200U combines high sensitivity with a wide dynamic measurement range making it ideal for ambient air quality, and other low-level applications.

— With NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- Lifetime technical support by phone and email
- All other T Series instrument platform features
- Standard two-year warranty





T200U Specifications

Ranges	Min: 0 - 5 ppb full scale Max: 0 - 2,000 ppb full scale (selectable, independent NO, NO ₂ , NO _x ranges)
Measurement Units	ppb, μg/m ³ (selectable)
Zero Noise	< 25 ppt (RMS)
Span Noise	< 0.5% of reading (RMS) above 5 ppb
Lower Detectable Limit	< 50 ppt
Zero Drift	< 0.1 ppb/24 hours
Span Drift	< 0.5% of reading/24 hours
Response Time	< 70 seconds to 95%
Linearity	1% of full scale
Precision	0.5% of reading above 5 ppb
Sample Flow Rate	1,000 cc/min ±10%
Power Requirements	100V-120V, 220V-240V, 50/60 Hz, Typical power 110W
Analog Output Ranges	10V, 5V, 1V, 0.1V (selectable)
Recorder Offset	±10%
Included I/O	1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs
Optional I/O	1 x USB com port 1 x RS485 4 x digital alarm outputs Multidrop RS232 3 x 4-20mA current outputs
Operating Temperature Range	5 - 40°C 20 - 30°C (with US EPA Equivalency)
Dimensions (HxWxD)	7" x 17" x 23.5" (178 x 432 x 597 mm)
Weight	Analyzer: 40 lbs (18 kg) External pump: 22 lbs (10 kg)
Certifications	US EPA: RFNA-1194-099
Certifications	US EPA: RFNA-1194-099

Specifications subject to change without notice. All specifications are based on constant conditions.



9970 Carroll Canyon Road • San Diego, CA 92131 Ph. 858-657-9800 Fax 858-657-9816 Email api-sales@teledyne.com For more information about the Teledyne API family of monitoring instrumentation products, call us or visit our website at:

www.teledyne-api.com

© 2019 Teledyne API Printed documents are uncontrolled. SAL000049G (DCN 8120) 07.15.19

